

ITEM	SYMBOL	QTY	MANUFACTURER	CATALOG NUMBER	DESCRIPTION
1	EN	1	HOFFMAN	A48H3612SSLP	ENCLOSURE, NEMA 4X, 48" H X 36" W X 12" D, TYPE 304 STAINLESS STEEL.
2	EN	2	HOFFMAN	A48P36AL	SUBPANEL FOR 48" H X 36" W ENCLOSURE, ALUMINUM.
3	EN	1	HOFFMAN	ANADFK	DEAD FRONT PANEL KIT FOR ENCLOSURE, W/O PANEL.
4		0	HOFFMAN	AL3A	LATCH KIT FOR SINGLE DOOR ENCLOSURE, 1 POINT LATCHING, NON-LOCKING.
5	CB205	1	CARLOS GAVAZZI	GMB631PD10	CIRCUIT BREAKER, 240 VAC, 10 A, 1 POLE, D CURVE, DIN RAIL.
6	CB240 ...	2	CARLOS GAVAZZI	GMB631PC5	CIRCUIT BREAKER, 240 VAC, 5 A, 1 POLE, C CURVE, DIN RAIL.
7	FB308 ...	6	PHOENIX	3046388	FUSABLE DISC. TERMINAL BLOCK, 400 V, 20 A, #12 AWG, TYPE UT2.5-TG.
8	FB308 ...	6	PHOENIX	3047141	END COVER FOR UT2.5-TG FUSABLE DISC. TB, TYPE D-UT 2.5/4-TWIN.
9	FB308 ...	6	PHOENIX	3209248	FUSE PLUG, LED TYPE, 30 VDC MAX, 1 POLE, TYPE P-FU5X20LED24-5.
10	FB336	1	BUSSMANN	GMA-8	FUSE, FAST ACTING, GLASS 5X20 MM, 125 V, 8 A.
11	FB308 ...	5	BUSSMANN	GMA-5	FUSE, FAST ACTING, GLASS 5X20 MM, 125 V, 5 A.
12		0	BUSSMANN	GMA-2	FUSE, FAST ACTING, GLASS 5X20 MM, 125 V, 2 A.
13	PS302	1	PHOENIX	2907160	UNINTERRUPTIBLE POWER SUPPLY (UPS), 24 VDC IN & OUT, 5 AMPS.
14	BA308	1	PHOENIX	2320319	UPS BATTERY, LEAD-ACID, 24 VDC, 7.2 AMP-HOURS, INTERNALLY FUSED.
15	SEL PAC	1	SEL	2411P2BDBBDB6X063120	PROGRAMMABLE AUTOMATION CONTROLLER, 24 VDC, 34DI, 7DO, 4AI, 4AO.
16	UN452 (OPTION)	1	SEL	3505XDEX0XAXX211X1XXXXXX	AUTOMATION CONTROLLER, SEL-3505 RTAC, 24 VDC.
17	UN1202	1	IDEC	FL1F-H12RCA	SMART RELAY, 24 VAC/VDC, 8 INPUTS, 4 RELAY OUTPUTS.
18	UN508	1	SIERRA WIRELESS	RV50X	CELLULAR ROUTER, AIRLINK RV50 INDUSTRIAL LTE GATEWAY, 24 VDC.
19	UN508	1	SIERRA WIRELESS	6000659	DIN RAIL MOUNTING BRACKET FOR AIRLINK RV50 INDUSTRIAL LTE GATEWAY.
20		0	SEL	3061#JBCB	CELLULAR ROUTER, SEL-3061, 24 VDC.
21	UN508	1	VERIZON	VZW 4G SIM	4G STANDARD SIM CARD.
22	ANTENNAS	2	PANORAMA ANTENNAS	LPB-7-27-5SP	MULTI-FREQUENCY ANTENNAE, LOW PROFILE, HOLE MOUNT.
23	UN477 (OPTION)	1	PHOENIX	2891929	ETHERNET SWITCH, 10/100BASE-TX, 8 RJ45 PORTS, 24 VDC, DIN RAIL.
24	ETM702 ...	3	ENM	T40A45	HOUR METER, 6 DIGIT, 1.68" ROUND, 10-80 VDC, SNAP-ON RING MOUNT.
25	CR839	1	IDEC	RR3B-UL-24VDC	CONTROL RELAY, 240 V, 10 A, 24 VDC COIL, 3 NO 3 NC, BLADE TYPE W/ PL.
25A	CR839	1	IDEC	SR3B-05	RELAY SOCKET, 11 PIN, BLADE TYPE FOR 3PDT RELAYS, DIN RAIL.
26	CR612 ...	7	IDEC	RR2P-UL-24VDC	CONTROL RELAY, 240 V, 10 A, 24 VDC COIL, 2 NO & 2 NC, WITH PL.

ITEM	SYMBOL	QTY	MANUFACTURER	CATALOG NUMBER	DESCRIPTION
27	CR612 ...	7	IDEC	SR2P-06	RELAY SOCKET, 8 PIN, TUBE TYPE FOR DPDT RELAYS, DIN RAIL.
28	CR406 ...	14	PHOENIX	2966171	CONTROL RELAY, 24 VDC COIL, 1 NO/NC, DIN RAIL MOUNT.
29	ISO952	1	PHOENIX	2901998	SIGNAL ISOLATOR, 4-20 MADC INPUT AND OUTPUT, 24 VDC POWER.
30	HN1139 (SHIP LOOSE)	1	EDWARDS	877-G1	HORN, 24 VDC, NEMA 4X, SURFACE MOUNT, WITH ENC, 101 DB AT 10 FT.
31	LT1141 (SHIP LOOSE)	1	EDWARDS	125LEDJR24D	STROBE, 24 VDC, NEMA 4X, FLASHING RED, CONDUIT MOUNT, 0.1 AMPS.
32	PL1232	1	SQUARE D	9001KP35A31	PILOT LIGHT, FULL VOLTAGE TYPE, 30 MM, 24 V, PLASTIC AMBER LENS.
33	PB1129 ...	2	SQUARE D	9001KR1B	PUSHBUTTON, 600 V, 30 MM, BLACK FLUSH HEAD OPERATOR, ADD CONTACTS.
34	SS1003 ...	3	SQUARE D	9001KS42B	SELECTOR SWITCH, 600 V, 3 POSITION, ADD CONTACTS, XOO-OOX TYPE.
35	PB/SS	14	SQUARE D	9001KA1	CONTACT BLOCK, 600 V, 10 A, 1 NO & 1 NC CONTACT.
36	SP209	1	PHOENIX	2910349	SURGE PROTECTION DEVICE, TYPE 1, 120 VAC 2 WIRE PLUS GROUND.
37	SP952	1	PHOENIX	2906781	SURGE PROTECTION DEVICE, FOR ANALOG 0-20 MILLIAMP SIGNALS.
38	TB	125	PHOENIX	3044571	TERMINAL BLOCK, TYPE UT4-QUATTRO, 600 V, 30 A, DUAL BOX LUGS, #10 AWG.
39	TB212	1	EUROSTRIPS	TS2.5/10WP-40.210	TERMINAL STRIP, 300 V, 30 A, BOX LUGS, #18-#12 AWG, 10 POINT.
40	TBAC	14	PHOENIX	3044597	GROUNDING TERMINAL BLOCK, TYPE UT4-QUATTRO-PE, DUAL LUGS, #12 AWG.
41	FN212	1	COMMERCIAL		FAN, 115 VAC, 110 CFM, 3000 RPM, 120 MM SQUARE.
42	FN212	2	COMMERCIAL		FAN FINGER GUARD, 200 MM SQUARE.
43	FN212	1	COMMERCIAL		POWER CORD FOR 200 MM SQUARE FAN.
44	FN212	1	HOFFMAN	ABRKT4	BRACKET FOR 4" PANEL CIRCULATION FAN, 12" X 6" X 1", GRAY.
45	HT215	1	STEGO	060110-00	PANEL HEATER, 120 VAC, 100 WATTS, WITH TSTAT, 59-41 DEGREES OFF-ON.
45A	SW614	1	SQUARE D	9007AP221	LIMIT SWITCH, 600 V, PLUNGER TYPE, SPDT CONTACTS.
46	DR240	1	PHOENIX	5600462	DUPLEX RECEPTACLE, 120 VAC, 15 A, BEIGE, NEMA 5-15R, GFCI, DIN RAIL.
47	NP	1	BRADY	CST1023-120	SIGN, FIBERGLASS, 3 1/2" X 5": "DANGER - 120 VOLTS"
48	NP	1	ELECTRIC MACHINE CONTROL, INC.	NP-EMC	NAMEPLATE, CAST ZINC, 3" BY 6": "ELECTRIC MACHINE CONTROL".